

ELEVAN[®]40 Tires

Max. working height		4,00 m
Max capacity		220 kg
Number of people		1
Use		Internal - External
A	Closed machine height	1750 mm
B	Minimum platform height	290 mm
C	Maximum platform height	1950 mm
D	Base overall dimensions	1780 mm
E		715 mm
G	Cage dimensions	685 mm
H		580 mm
Machine weight		475 kg
Driving wheels size		Ø 186 x 60 mm
Idle rear wheels size		Ø 150 x 40 mm

PICKING PLATFORM

I	Dimensions	595 mm
L		545 mm
Adjustment		Electric
J	Stroke	1430 mm
Min. height from the ground		60 mm
Maximum height from the ground		2800 mm
Capacity		120 kg

PERFORMANCE

Power supply		24V
Batteries		2 AGM 12V 45 Ah*
Battery charger		115V–230V 50/60HZ
M1	Maximum climbing ability	15%
M2	Surmountable landing slope	15%
R1	Internal turning radius	900 mm
R2	External turning radius	2200 mm
Max. speed (rising – descending)		0,15 m/s
Maximum shifting speed		5 km/h
N	Maximum pressure for wheel at full load **	2,3 kN

* There is an intermediate step.

** Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).



Complies with European regulations for man-up forklift trucks. UNI EN ISO 3691-1.
In assessing compliance, only those standards whose proposed measures have been implemented were considered and only if a corresponding risk does indeed exist.

