



ELEVAH[®] 80 MOVE picking



ELEVAH® 80 MOVE picking

| | | |
|-----------------------------|-------------------------------|---------------------|
| Max. working height | | 7,78 m |
| Max capacity | | 200 kg |
| Number of people | | 1 |
| Use | | Internal - External |
| A | Closed machine height | 1980 mm |
| B | Minimum platform height | 650 mm |
| C | Maximum platform height | 5780 mm |
| D | Base overall dimensions | 1280 mm |
| E | | 1780 mm |
| F | | 780 mm |
| G | Cage dimensions | 640 mm |
| H | | 710 mm |
| Machine weight | | 860 kg |
| K | Fixed picking tray dimensions | 440 mm |
| L | | 740 mm |
| Fixed picking tray capacity | | 20 kg |
| Drive wheels dimension | | Ø 220 x 65 mm |
| Swivel wheels dimensions | | Ø 200 x 50 mm |



PICKING PLATFORM

| | | |
|--------------------------------|------------|------------|
| Adjustment | | Electrical |
| Stroke | | 600 mm |
| Min. height from the ground | | 1030 mm |
| Maximum height from the ground | | 6830 mm |
| I | Dimensions | 500 mm |
| J | | 680 mm |
| Capacity | | 100 kg |

PERFORMANCE

| | | |
|---|--|--------------------------------|
| Power supply | | Electrical |
| Batteries | | Lead-Acid Batteries 12V 105 Ah |
| Battery charger | | 110V – 220V 50/60HZ |
| M | Maximum climbing ability | 15% |
| Climbing ability at height | | 2,5% |
| Internal turning radius | | 0 |
| External turning radius | | 1095 mm |
| Max. speed (rising – descending) | | 0,2 m/s |
| Maximum speed (with basket on the ground) | | 5 km/h |
| N | Maximum pressure for wheel at full load* | 3,7 kN |
| Work cycles (with fresh batteries) ** | | Ca. 130 |

* Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).

** By work cycle we mean a self-propelled movement of 20 m with a full ascent to and descent from the maximum height and with adjustment of the loading platform.

CE Complies with European regulations for man-up forklift trucks. UNI EN ISO 3691-1.

