

ELEVAH[®] 5 inox



ELEVATOR[®] 5 INOX

Max. working height	5,15 m	
Max capacity	200 kg	
Number of people	1	
Use	Internal	
A	Closed machine height	1690 mm
B	Min. height from the ground*	289 mm
C	Maximum platform height	3150 mm
D	Base overall dimensions	980 mm
E		700 mm
F	Cage dimensions	685 mm
G		600 mm
Machine weight	580 kg	
Drive wheels dimension	Ø 186 x 60 mm	
Swivel wheels dimensions	Ø 150 x 40 mm	



PERFORMANCE

Power supply	Electrical 24 V	
Batteries	2 Trojan Lead-Acid 12V 105 Ah	
Battery charger	115V – 230V 50/60HZ	
H	Maximum climbing ability	15%
	Climbing ability at height	2,5%
	Internal turning radius	0
	External turning radius	1050 mm
	Max. speed (rising – descending)	0,2 m/s
	Maximum shifting speed	0,70 m/s
	Maximum shifting speed at height	0,25 m/s
I	Maximum pressure for wheel at full load**	2,7 kN
	Work cycles (with fresh batteries) ***	100

* There is an intermediate step.

** Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).

*** By work cycle we mean a self-propelled movement of 20 m with a full ascent to and descent from the maximum height and with adjustment of the loading platform.



Compliant with **EN280** rule.
Approved for indoor use or outdoor use in the absence of wind.

