

Mecaplús, S.L.
Torre del Catalán s/n
22535 Esplús - Huesca - España
Tel. +34 696 49 88 80
administracion@mecaplus.es
www.mecaplus.es

Aerial platform



## **EMECAPLUS**

## Standars features

- Self-levelling undercarriage up to 10° slope in both directions, also diagonally
- Pivotable work platform -90° +90
- Large service door for loading in to the basket with a forklift
- Rexroth radial piston motor MCR-F
- Emergency system to lowering the boom
- Kubota engine that meets the latest emissions requeriments Stage V
- Tool box in the basket



## **Options**

- Option: ECO Bi fuel
- Generator 3.5kw 220v
- Battery box
- Boom movement limiting key
- Fire extinguishers and fire blanket
- Towing ball
- Drum transporter
- Anti-Crushing
   Anti-collision warning (sonars) in basket
   when the distance to tunnel roof will be
   too short
- Additional air filter for maximum protection of the engine
- Protective bellows on all hydraulic cylinders
- Powerful oil cooler for hydraulic oil
- LED storbe light 4x led orange R65 R10
- Work light / driving light LED Worklamp 16x LED Square
- Removable cable pulley on the basket

Specifications	
Working height:	9.9 m
Platform height:	7.9 m
Machine height with drum transporter:	2,7 m
Machine width:	2,3 m
Machine length with drum transporter:	5,4 m
Net weight:	7700 kg
Net weight Bi fuel:	8000 kg
Basket capacity:	600 / 1000 kg
Basket size :	2 m x 3 m
Maximum horizontal reach :	5,9 m
Turntable rotation:	340°
Cross axis inclination:	3º
Longitudinal axis inclination :	3º
Gradeability:	45%
Basket rotation :	+90º/-90º
Electrical system:	12V
Motor :	Kubota V1505 CRT
	/ Bi fuel

## Self leveling system I.A.D.R

Cross axis  $10^{\circ} = 17.6\%$  of slope Longitudinal axis  $10^{\circ} = 17.6\%$  of slope

Dynamic leveling with the articulated boom in any position up to 9.9m height.

It provides a dynamic and controlled response of the machine axes to avoid the three-wheel effect, with the articulated boom in any position up to 9.9 m height.

