ZOONLON VERTICAL MAST LIFTS ZMP09J

Comply with CE/GB Standard

HIGHLIGHTS

- ► Large work range, leading in industry
- ▶ AC motor drive system, saving energy and maintenance free
- ▶ Mechanic pothole mechanism, easy to pass through
- ▶ Compact size with zero tailswing, easy to access narrow space
- ► Standard side fork hole, safe to transfer

FEATURES

Standard Features

| Autobrake system | Flashing beacon | |
|----------------------------|----------------------------------|--|
| Proportional control | Active pothole protection system | |
| All motion alarm | Horn | |
| Charging protection system | Differential control | |
| Self-closing entry gate | Hour meter | |
| Maintenance-free battery | On-board diagnostic | |
| Drivable at full height | Over tilt protective system | |
| Emergency descent system | Forklift pockets | |
| Emergency stop button | Load sensing system | |
| | | |

Accessories & Options

- ► Platform work light
- AC power to platform
- GPS
- Remote monitor and rental management platform



Phone: 0086(731)-88353680 0086(731)-88250971 E-mail: awp@zoomlion.com Add: 701 Xulong Nan Lu, Xiangjiang New District, Changsha Hunan, China Web; www.zoomlion-access.com



VERTICAL MAST LIFTS

ZMP09J

Comply with CE/GB Standard

| Model | ZMP09J | |
|--|---------------------|---------|
| | Imperial | Metric |
| | Size | |
| Max Work Height | 36ft 10in | 11.2m |
| Max Platform Height | 30ft 2in | 9.2m |
| Max Platform Horizontal Outreach | 10ft 7in | 3.23m |
| Max Up and Over Height | 25ft 6in | 7.75m |
| A - Stowed Length | 8ft 10in | 2.7m |
| B - Stowed Width | 3ft 3in | 1m |
| C - Stowed Height | 6ft 6in | 1.99m |
| D - Platform Length | 2ft 6in | 0.76m |
| E - Platform Width | 3ft 3in | 0.99m |
| F - Wheelbase | 3ft 11in | 1.2m |
| G - Ground Clearance (Stowed) | 2.6in | 0.065m |
| H - Ground Clearance (Raised) | 0.6in | 0.015m |
| | Performance | |
| Platform Capacity | 441lb | 200kg |
| Max. Number of Workers (indoor/outdoor) | 2/1 | 2/1 |
| Drive Speed (Stowed) | 2.80mph | 4.5km/h |
| Drive Speed (Raised) | 0.31mph | 0.5km/h |
| Turning Radius (Inside) | 8in | 0.2m |
| Turning Radius (Outside) | 5ft 4in | 1.61m |
| Lifting Motor | AC 24V/3kW | |
| Drive Motor | AC 24V/2x0.7kW | |
| Up/Down Time | 42/40s | |
| Gradeability | 25% (14°) | |
| Max. Working Slope (Lateral/Vertical) | 2.5° | |
| Jib Rotation | 125° | |
| Tail Swing | 0 | |
| Tire | Solid seamless tire | |
| | Power | |
| Battery | 4×6√240Ah | |
| Charger | 24V/30A | |
| | Weight | |
| Gross | 6600lb | 2995kg |





